


Low frequency



- very flexible and pliable cable for non-stationary electrical loads
- Connection of lamps, monitors, computers, printers, copiers, mobile devices and much more
- plastic-coated aluminium strip, two-wire copper min. 0.34 mm<sup>2</sup> fine wire
- Shielding (alternating electric field, 50 Hz mains voltage)
- Reduction of the alternating magnetic field through twisting
- Protection class 1 - with PE protective wire
- Shielded flexible cable for connection of mobile devices moulded Schuko plug and cold appliance socket.
- The cold appliance connection cable KGL 2.0 is preferably used for additional shielding of PCs and peripheral devices such as printers, monitors, scanners and the like.



**Order-No.: 300087 - 41-2806**  
Short-Desc.: KGL 2,0 sw

### Cold appliance cable

#### KGL 2,0 black

#### Technical data

Length:	2,0 Metre
Colour:	black
Operating voltage: (max.)	250 VAC / 50Hz
Load: (max.)	10A acc. IEC 320-1
Reduction of alternating magnetic field:	Beat 15 (single wires twisted against each other 15x per metre)
Insulation cable: Shield:	Polyvinyl chloride Plastic-coated aluminium strip, two-wire Cu min 0.34 mm <sup>2</sup> fine wire
Protection class:	1 (with protective wire)
Cross-section:	3 x 1.0 mm <sup>2</sup> + shielding wire min. 0.34 mm <sup>2</sup> fine wire
Diameter:	Ø 7,1 mm ± 0,2 mm
Angle protection-contact plug:	moulded, CEE-Norm 7/VII, DIN 49441
Power socket:	moulded, IEC 320, C 13, EN 60320

#### Scope of application

Very flexible and bendable cable for non-fixed electrical consumers

Connecting monitors, computers, scanners, printers, copiers and other mobile devices

#### Scope of delivery

Cold appliance cable KGL 2,0

